



Balanced Optic



Microprismatic Optic



Opal Diffuser

## Avic Pro

Tunable White

Wire suspended LED pendant luminaire with direct/indirect distribution.

Product: **AVP-2\*\*TW-\***

### Light Technique

- Colour temperature: Tunable White 2700-5700K.
- Colour rendering index CRI>80.
- 100,000 h lifetime (L70 B10).

### Luminaire Housing

- Indirect cover made of clear polycarbonate.
- Visible height only 25mm (68mm total height includes driver housing on back).

### Operating and Assembly Technology

- Electrical connection with plug-in terminal up to 2.5mm<sup>2</sup> with loop-in function.
- "Y" wire suspension with transparent lead, pre-assembled, 1500mm length.

### Part Code Variations

\* Optic

**B** – Balanced optic.

**M** – Microprismatic optic

**O** – Opal diffused

\* Paint Finish

**B** – Black RAL 9005

**S** – Silver RAL 9006

**W** – White RAL 9010

\* Control Protocol

**D** – DALI DT8

**B** – Bluetooth Enabled (Wireless)

Light Technique	Balanced	MPO	Opal
System Wattage (W)	46 W	46 W	46 W
Luminaire luminous flux (Llm)	5,530 Llm	5,518 Llm	5,624 Llm
System efficacy (Llm/W)	120 Llm/W	120 Llm/W	122 Llm/W
Unified Glare Rating (UGR)	17.9	17.3	20.2

### Operating Technology

Operation mode	See part code suffix
Connector	Plug-in terminal

### Dimensions

Length L	1230 mm
Width W	284 mm
Height H	68 mm
Total weight	8.6 kg

